



ULTIMA⁺ OP

ULTIMA⁺ OP not only offers a finely textured and durable surface with a brighter “blue-white” colour for high light reflectance, but is also C2C Bronze certified and provides Class A sound absorption, making it ideal for open plan areas.

Key features

- Excellent sound absorption: 1.00 α_w
- Very high light reflectance: 87%
- Better finish and more durable edges
- C2C Bronze certified / ISO 5 / A+
- 30 year system guarantee

Application areas

Ideal for open spaces (call centres, cafeterias..).

OFFICE
PwC Headquarters (PL)
ULTIMA⁺ OP MicroLook 90



EDGE DETAIL	BOARD		TEGULAR		MICROLOOK 90		
THICKNESS (mm)	20		20		20		
MODULE (mm)	600 x 600 7682M	600 x 600 7678M	600 x 600 7679M	600 x 600 7685M	600 x 550 7714M	600 x 600 7685M	600 x 600 7686M
	675 x 675 7683M	675 x 675 7679M	675 x 675 7680M	675 x 675 7686M	1200 x 600 7687M	1200 x 600 7687M	1200 x 600 7687M
	1200 x 600 7684M	1200 x 600 7680M			1500 x 600 7708M		
SUSPENSION SYSTEMS	Prelude 24 XL ² /TL ² Prelude 24 Sixty ² XL ² /TL ²		Prelude 24 XL ² /TL ² Prelude 24 Sixty ² XL ² /TL ²		Prelude 15 TL/XL ² Interlude HRC XL ² Silhouette 6mm XL ²		

COLOURS



Global White

SUSTAINABILITY



17



A+



E1



IBU

ACOUSTICS



EN ISO 10848-2
& EN ISO 717-1



EN ISO 140-3
& EN ISO 717-1



EN ISO 354
& EN ISO 11654

Hz α_w

	D _{nfw}	R _w	α_w	Class	NRC	125	250	500	1000	2000	4000
Board, Tegular, MicroLook 90	25 dB	10 dB	1.00	A	0.95	0.40	0.80	1.00	0.95	1.00	1.00

FIRE REACTION



EEA Euroclass A2-s1, d0
EN 13501-1

RUS KM1 (G1, V1, D1, T1)
FZ 123

OTHER PERFORMANCES & FEATURES



87%



95% RH



ISO 5



30 YEAR
system
guarantee



$\lambda = 0.037$ W/m K



3.2 kg/m²



ISO 14644-1



BIM
READY

CUSTOM OPTIONS



Dimensions